



With the addition of the EVID flush mount, in-wall speaker products, the EVID line now offers an audio solution for any background or foreground installation task. Sonically superior and aesthetically pleasing, the EVID line has no equal.

Designed to work seamlessly with all EVID subwoofers.

The EVID FM series of flush mount, in-wall speaker systems are leading the next generation of high performance background and foreground speaker system products. They are a truly innovative design that provides the performance consistency and easy installation that users and installers demand. Their unique construction and acoustic design deliver both superior sound quality and an easy, no hassle installation experience.



FM4.2

The FM4.2 features an attractive design and compact profile. It provides excellent performance for small and mid sized rooms, and is designed to work seamlessly with all EVID subwoofers. A 4" woofer, 4" passive radiator, and a 1" tweeter provide high quality sound. The fully sealed enclosure guarantees consistent performance in any installation.

FM6.2

The FM6.2 provides very high power handling and outstanding audio performance in a fully sealed, in-wall speaker system package. Perfect for installations in larger rooms, it features a 6" woofer coupled with a 6" passive radiator for extended bass response. A 1" dome tweeter gives clean sound out to 20 kHz. It is all housed in a shallow, fully sealed enclosure for consistent audio quality and superior sound isolation from adjacent rooms.





Common Key Features:

- Fully sealed enclosures provides superior sound isolation from adjacent rooms.
- Tuned passive radiator design ensures consistently superior performance in any installation.
- Either 70v/100v or 8 ohm operation is standard on both models. No need to buy or stock special versions.
- Shallow profile allows installation virtually anywhere.
- Secure phoenix style pass through connectors for easy wiring and installation.
- Four point "quick mounting" tabs provide fast easy installation in any wall cavity.
- The transformer is mounted on the rear can surface to further enhance stiffness.
- Specially designed ribbed back can is designed to eliminate flexing.



EVID In-Wall Speaker Product Specifications:

	EVID FM4.2	EVID FM6.2
Freq. Response (-3 dB):	70 Hz - 20 kHz	60 Hz - 20 kHz
Freq. Range (-10 dB):	52 Hz - 20 kHz	52 Hz - 20 kHz
Axial Sensitivity:	87 dB (SPL 1W/1m)	90 dB (SPL 1W/1m)
Impedance:	8 ohms nominal (transformer bypass)	8 ohms nominal (transformer bypass)
Crossover Frequency:	3.6 kHz	3.3 kHz
Rec. Highpass Frequency:	70 Hz	60 Hz
HF Transducer:	1 in. (25.4 mm)	1 in. (25.4 mm)
LF Transducer:	4 in. (101.6 mm)	6.5 in. (165.1 mm)
Passive Radiator:	4 in. (101.6 mm)	6.5 in. (165.1 mm)
Transformer Taps:	70V: 1.75, 3.75, 7.5, 15, or 30W 100V: 3.75, 7.5, 15, or 30W Bypass: 8 ohms nominal	70V: 7.5, 15, 30, or 60W 100V: 15, 30, or 60W Bypass: 8 ohms nominal
Connectors:	4 pin phoenix style terminals	4 pin phoenix style terminals
Enclosure Material:	Baffle: UL 94V-O rated ABS Backcan: Zinc plated steel	Baffle: UL 94V-O rated ABS Backcan: Zinc plated steel
Grille:	Perforated powder coated steel with safety tether	Perforated powder coated steel with safety tether
Mounting System:	Integrated toggle anchors	Integrated toggle anchors
Support Hardware:	Cutout template, Paint Shield	Cutout template, Paint shield
Dimensions:	349.9mm x 188.3mm x 96.5mm (13.77" x 7.42" x 3.80")	465.4mm x 256.4mm x 100.3mm (18.32" x 10.09" x 3.95")
Net Weight (Each):	2.9 kg (6.5 lb)	5.8 kg (12.7 lb)
Shipping Weight (Pair):	6.8 kg (15.0 lb)	12.9 kg (28.4 lb)

Bosch Communications Systems
Americas—Headquarter Americas
Telex Communications, Inc.
12000 Portland Ave South,
Burnsville, MN 55337, USA
USA—Ph: 1-800-392-3497
Fax: 1-800-955-6831
Canada—Ph: 1-866-505-5551
Fax: 1-866-336-8467
Latin America—
Ph: 1-952-887-5532
Fax: 1-952-736-4212

Europe, Africa & Middle-East
Headquarter EMEA
EVI Audio GmbH
Hirschberger Ring 45, D-94315
Straubing, Germany
Phone: +49 9421 706-0,
Fax: +49 9421 706-265

France: EVI Audio France S.A.,
Parc de Courcerin,
Allée Lech Walesa,
F 77185 Lognes, France
Phone: +33 1-6480-0090
Fax: +33 1-6006-5103

UK: Shuttlesound,
4 The Willows Centre,
Willow Lane, Mitcham,
Surrey CR4 4NX, UK
Phone: +44 208 646 7114
Fax: +44 208 254 5666

Asia & Pacific Rim—
Headquarter Asia
Singapore: Telex Communications
(SEA) Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Tel: (65) 6319 0621
Fax: (65) 6319 0620

Japan: EVI Audio Japan Ltd.
5-3-8 Funabashi, Setagaya-Ku,
Tokyo, Japan 156-0055
Phone: +81 3-5316-5020,
Fax: +81 3-5316-5031

Hong Kong: Telex EVI Audio
(HK) Ltd.
Unit 5,1/F, Topsail Plaza
11 On Shum Street
Shek Mun, Shatin HK
Phone: +852 2351-3628,
Fax: +852 2351-3329

Bosch Communications Systems
Telex EVI Audio
(Shanghai) Co., Ltd.
Room 3105-3109,
Tower 1 Office Building,
218 Tian Mu Xi Rd.,
Shanghai, China
Postal Code: 200070
Tel: +86 21-6317-2155
Fax: +86 21-6317-3025

Live For Sound
www.electrovoice.com

